



川磊电子科技
ThreeLayer Technologies, Inc.
專業電感製造商

南充新川电子科技有限公司

ThreeLayer Scientific-Technics Co.,Ltd



产品承认书

SPECIFICATION FOR APPROVAL

客户名称 -----
CUSTOMER NAME.

产品类型 SMD Power Inductors
PRODUCT TYPE

客户料号 -----
CUSTOMER PN

川磊料号 CLNR-252012- SERIES
OURS PN

文件编号 SP-21022501
FILE NO.

客户承认/ <i>CUSTOMER ACCEPTED</i>		
承认 <i>APPROVED</i>	确认 <i>CHECKED</i>	承办 <i>DESIGN</i>
批注/ <i>REMARK</i>		


批准 <i>APPROVED</i>	确认 <i>CHECKED</i>	作成 <i>DESIGN</i>
程志华	何利	张莉萍

生产工厂：南充川磊电子科技有限公司
销售公司：南充新川电子科技有限公司
业务专线：0817-211163/18681773184
邮 件：threelayer_sales@163.com
地 址：四川省南充市顺庆区潞华工业园区华生东路




客户名称 CUSTOMER	-----	客户品名 CUSTOMER P/N	-----	版别 REV.	1.0
产品类型 PRODUCT TYPE	SMD Power Inductors	新川品名 OURS P/N	CLNR-252012- SERIES	文件编号 FILE NO.	SP-21022501

一.尺寸图/DIMENSION (单位/UNIT : mm)



ITEM	A	B	C	D	E	H	I	J	
DIM	2.5	2.0	1.25	0.8	0.9	2.0	1.1	0.6	
TOLE	±0.25	±0.25	Max	±0.3	±0.3	Typ	Typ	Typ	

二.电路图/CIRCUIT DIAGRAM



三.注意事项/NOTE :

四.电气特性/ELECTRICAL CHARACTERISTIC

Part Number	Inductance (uH)	Tolerance	Test Frequency(Hz)	DCR (Ω) Max	IDC1 (A) Max.	IDC2 (A) Max.	MARK
CLNR-252012-R47□	0.47	N	1M/0.25V	0.061	3.82	2.15	A
CLNR-252012-R68□	0.68	N	1M/0.25V	0.074	3.28	1.95	B
CLNR-252012-1R0□	1.0	N	1M/0.25V	0.09	2.59	1.93	C
CLNR-252012-1R2□	1.2	N	1M/0.25V	0.129	2.38	1.46	D
CLNR-252012-1R5□	1.5	N	1M/0.25V	0.147	2.24	1.4	E
CLNR-252012-2R2□	2.2	N	1M/0.25V	0.216	1.85	1.15	F

客户名称 CUSTOMER	-----	客户品名 CUSTOMER P/N	-----	版别 REV.	1.0
产品类型 PRODUCT TYPE	SMD Power Inductors	新川品名 OURS P/N	CLNR-252012- SERIES	文件编号 FILE NO.	SP-21022501

四.电气特性/ELECTRICAL CHARACTERISTIC

Part Number	Inductance (uH)	Tolerance	Test Frequency(Hz)	DCR (Ω) Max	IDC1 (A) Max.	IDC2(A) Max.	MARK
CLNR-252012-3R3□	3.3	M N	1M/0.25V	0.264	1.61	1.04	G
CLNR-252012-4R7□	4.7	M N	1M/0.25V	0.377	1.12	0.84	H
CLNR-252012-5R6□	5.6	M N	1M/0.25V	0.538	1.11	0.73	I
CLNR-252012-6R8□	6.8	M N	1M/0.25V	0.581	0.98	0.69	J
CLNR-252012-8R2□	8.2	M N	1M/0.25V	0.658	0.98	0.65	N
CLNR-252012-100□	10	M N	1M/0.25V	0.69	0.79	0.62	K
CLNR-252012-120□	12	M N	1M/0.25V	1.075	0.78	0.51	O
CLNR-252012-150□	15	M N	1M/0.25V	1.591	0.68	0.42	L
CLNR-252012-220□	22	M N	1M/0.25V	1.976	0.53	0.38	M

(1) Specify the inductance tolerance, K(±10%),M(±20%),N(±30%)

(2).IDC1:Base on temp.rise & ΔL/L0A 30% Typ

(3).IDC2:Temp.rise 40°C Typ

(4).Operating temp.: -40°C to +125°C

(5).Storage temp.: -20°C up to +40°C, 75% RH max.

五.材料清单/MATERIAL LIST

NO.	ITEM	DESCRIPTION
1	CORE	FERRITE
2	WIRE	P180 G1
3	ADHESIVE	NR-3614
4	TIN	107H
5	INK	BLACK


客户名称 CUSTOMER	-----	客户品名 CUSTOMER P/N	-----	版别 REV.	1.0
产品类型 PRODUCT TYPE	SMD Power Inductors	新川品名 OURS P/N	CLNR-252012- SERIES	文件编号 FILE NO.	SP-21022501

六.可靠性测试/RELIABILITY TESTING

Operating Temperature	- 40 to +125 °C (Contain HeatiDCR (mΩ) Max.
Appearance Inspection	No external defects by visual inspection
Terminal Strength	After soldering , between copper plaet and terminals of coils , push in two directions of X , Y with standing 10N(1.02kg) for10+/-2 sec. Terminal should not peel off. (Refer to figure at right)
Heat endurance of reflow soldering	Refer to figure
Insulating resistance	Over 100 MΩ at 100V D.C . between wire and core
Dielectric Strength	Apply at 0.5KV 3mA for 1 minute between wire and core
Temperature characteristics	Inductance coefficient (0~2,000) × 10 / °C (- 40~ + 125 °C)
Humidity characteristics	Inductance deviation within ± 10% , after 96 hours in 90~95% relative humidity at 40 ± 2 °C and 1 hours drying under normal condition

A test is made under the above mentioned condition , and it is kept for 2 hours in the normal



IR Reflow profile



Temperature and humidity . After that , no mechanical and electrical defect should be found .

客户名称 CUSTOMER	-----	客户品名 CUSTOMER P/N	-----	版别 REV.	1.0
产品类型 PRODUCT TYPE	SMD Power Inductors	新川品名 OURS P/N	CLNR-252012- SERIES	文件编号 FILE NO.	SP-21022501

七.编带规格/TAPING SPECIFICATIONS




Tape width	Distance	Pull-of force
8 mm	4 mm	10~120g


八.包装方式/PACKING LIST



轮盘：7'(直径178mm)
数量：2000PCS/盘



内盒/PE袋
数量：10000PCS/盒



外箱，数量：100000PCS/箱
不足整箱用内盒或填充物